

6.4" LED Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA



JS064LPNN / JS064LKNN

Model	JS064LPNN	JS064LKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	6.4" TFT LCD Module	6.4" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LB064V02	LB104V03
Display Color	6-bits, 262,144 colors	6-bits, 262,144 colors
Display Area	130.56 x 97.92 mm	130.56 x 97.92 mm
Brightness	1,000 cd/m ²	1,000 cd/m ²
Resolution	640 x 480 (VGA)	640 x 480 (VGA)
Contrast Ratio	900 : 1	900 : 1
Pixel Pitch (mm)	0.068 x 0.204	0.068 x 0.204
Viewing Angle	65°/65°(H) 50°/60°(V)	65°/65°(H) 50°/60°(V)
Response Time	25ms (Tr+Tf)	25ms (Tr+Tf)
Sync	TTL	TTL
Power Consumption	4W	6W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	145.50 x 111.50 x 6.00	145.50 x 111.50 x 6.00
Lamp Lifetime (HR)	30,000	30,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL064	JL064
Weight	134 g	234 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

