

17" CCFL Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Low Power Consumption
- * Optional Touch Systems
- * CCFL 12 Lamps
- * VGA to SXGA



JS170CPNN / JS170CKNN

Model	JS170CPNN	JS170CKNN
Display Type	LCD + Inverter	LCD + Inverter + AD/OSD Board
LCD Display	17" TFT LCD Module	17" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LM170E03	LM170E03
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	337.920 x 270.336 mm	337.920 x 270.336 mm
Brightness	1,200 cd/m ²	1,200 cd/m ²
Resolution	1280 x 1024 (SXGA)	1280 x 1024 (SXGA)
Contrast Ratio	800 : 1	800 : 1
Pixel Pitch (mm)	0.264 x 0.264	0.264 x 0.264
Viewing Angle	80°/80°(H) 75°/85°(V)	80°/80°(H) 75°/85°(V)
Response Time	5ms (Tr+Tf)	5ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	50W	55W
Temperature	Operation 0°C ~ +55°C Storage -20°C ~ +60°C	Operation 0°C ~ +55°C Storage -20°C ~ +60°C
Dimension(WxHxD)mm	358.50 x 296.50 x 16.00	358.50 x 296.50 x 16.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JC170	JC170
Weight	1,900 g	2,000 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

