

17" LED Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA to SXGA



JS170LPNN / JS170LKNN

Model	JS170LPNN	JS170LKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	17" TFT LCD Module	17" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LM170E03	LM170E03
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	337.920 x 270.336 mm	337.920 x 270.336 mm
Brightness	1,000 cd/m ²	1,000 cd/m ²
Resolution	1280 x 1024 (SXGA)	1280 x 1024 (SXGA)
Contrast Ratio	800 : 1	800 : 1
Pixel Pitch (mm)	0.264 x 0.264	0.264 x 0.264
Viewing Angle	80°/80°(H) 75°/85°(V)	80°/80°(H) 75°/85°(V)
Response Time	5ms (Tr+Tf)	5ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	30W	35W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	358.50 x 296.50 x 16.00	358.50 x 296.50 x 16.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL170	JL170
Weight	1,600 g	1,700 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)

JnM665	VGA + DVI + Audio(Optional)
JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)

OSD Button

5 Key	Power Switch Select(+,-) Down Up Menu
-------	---------------------------------------

Sunlight Readable LCD Specialist !!!

