

20.1" CCFL

Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Low Power Consumption
- * Optional Touch Systems
- * CCFL 12 Lamps
- * VGA



JS201CPNN / JS201CKNN

Model	JS201CPNN	JS201CKNN
Display Type	LCD + Inverter	LCD + Inverter + AD/OSD Board
LCD Display	20.1" TFT LCD Module	20.1" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LC201V02	LC201V02
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	408.0 x 306.0 mm	408.0 x 306.0 mm
Brightness	1,000 cd/m ²	1,000 cd/m ²
Resolution	640 x 480 (VGA)	640 x 480 (VGA)
Contrast Ratio	800 : 1	800 : 1
Pixel Pitch (mm)	0.2125 x 0.6375	0.2125 x 0.6375
Viewing Angle	89°/89°(H) 89°/89°(V)	89°/89°(H) 89°/89°(V)
Response Time	25ms (Tr+Tf)	25ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	63W	68W
Temperature	Operation 0°C ~ +55°C Storage -20°C ~ +60°C	Operation 0°C ~ +55°C Storage -20°C ~ +60°C
Dimension(WxHxD)mm	432.00 x 331.50 x 25.00	432.00 x 331.50 x 25.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JC201	JC201
Weight	3,200 g	3,300 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	
JnM665	VGA + DVI + Audio(Optional)
JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	
5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

