

26" Wide LED Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA to WXGA



JS26WLPNN / JS26WLKNN

Model	JS26WLPNN	JS26WLKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	26" Wide TFT LCD Module	26" Wide TFT LCD Module
Base Panel Supplier	AUO	AUO
Base Panel Model	T260WX02 VR/VQ	T260WX02 VR/VQ
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	575.769 x 323.712 mm	575.769 x 323.712 mm
Brightness	1,500 cd/m ²	1,500 cd/m ²
Resolution	1366 x 768 (WXGA)	1366 x 768 (WXGA)
Contrast Ratio	3,000 : 1	3,000 : 1
Pixel Pitch (mm)	0.4215 x 0.4215	0.4215 x 0.4215
Viewing Angle	89°/89°(H) 89°/89°(V)	89°/89°(H) 89°/89°(V)
Response Time	6.5ms (GTG)	6.5ms (GTG)
Sync	LVDS	LVDS
Power Consumption	70W	75W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	626.00 x 373.00 x 45.00	626.00 x 373.00 x 45.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL26W	JL26W
Weight	3,750 g	3,850 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

