

# 32" EEFL Specifications

JNM DISPLAY Co., Ltd.

## Key Features

- \* Sunlight Readable
- \* High Contrast Ratio
- \* Low Power Consumption
- \* Optional Touch Systems
- \* EEFL 23 Lamps
- \* VGA to WXGA



## JS320EPNN / JS320EKNN

Model	JS320EPNN	JS320EKNN
Display Type	LCD (Include Inverter)	LCD (Include Inverter) + AD/OSD Board
LCD Display	32" TFT LCD Module	32" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LC320WXN	LC320WXN
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	697.685 x 392.256 mm	697.685 x 392.256 mm
Brightness	1,000 cd/m <sup>2</sup>	1,000 cd/m <sup>2</sup>
Resolution	1366 x 768 (WXGA)	1366 x 768 (WXGA)
Contrast Ratio	1,100 : 1	1,100 : 1
Pixel Pitch (mm)	0.17025 x 0.51075	0.17025 x 0.51075
Viewing Angle	89°/89°(H) 89°/89°(V)	89°/89°(H) 89°/89°(V)
Response Time	8ms (GTG)	8ms (GTG)
Sync	LVDS	LVDS
Power Consumption	150W	155W
Temperature	Operation 0°C ~ +55°C Storage -20°C ~ +60°C	Operation 0°C ~ +55°C Storage -20°C ~ +60°C
Dimension(WxHxD)mm	760.00 x 450.00 x 48.00	760.00 x 450.00 x 48.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JE320	JE320
Weight	6,150 g	6,250 g
Optional	Transflective tech.	Glass Bonding Touch

*Specifications are subject to change without notice.*

Control(AD) Board (Optional)	
JnM665	VGA + DVI + Audio(Optional)
JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	
5 Key	Power Switch Select(+,-) Down Up Menu

**Sunlight Readable LCD Specialist !!!**

