

7" LED Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA to WVGA



JS070LPNN / JS070LKNN

Model	JS070LPNN	JS070LKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	7" TFT LCD Module	7" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LB070WV6	LB070WV6
Display Color	6-bits, 262,144 colors	6-bits, 262,144 colors
Display Area	152.40 x 91.44 mm	152.40 x 91.44 mm
Brightness	1,000 cd/m ²	1,000 cd/m ²
Resolution	800 x 480 (WVGA)	800 x 480 (WVGA)
Contrast Ratio	700 : 1	700 : 1
Pixel Pitch (mm)	0.1905 x 0.1905	0.1905 x 0.1905
Viewing Angle	70°/70°(H) 50°/60°(V)	70°/70°(H) 50°/60°(V)
Response Time	25ms (Tr+Tf)	25ms (Tr+Tf)
Sync	TTL	TTL
Power Consumption	7.50W	9.50W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	167.00 x 103.70 x 10.50	167.00 x 103.70 x 10.50
Lamp Lifetime (HR)	20,000	20,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL070	JL070
Weight	205 g	305 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

