

38" Stretch LED

Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA to 1366x400



JS38SLPNN / JS38SLKNN

Model	JS38SLPNN	JS38SLKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	38" Stretch TFT LCD Module	38" Stretch TFT LCD Module
Base Panel Supplier	STI	STI
Base Panel Model	SL4238ML-01	SL4238ML-01
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	930.250 x 272.400 mm	930.250 x 272.400 mm
Brightness	1,000 cd/m ²	1,000 cd/m ²
Resolution	1366 x 400	1366 x 400
Contrast Ratio	1200 : 1	1200 : 1
Pixel Pitch (mm)	0.227 x 0.681	0.227 x 0.681
Viewing Angle	89°/89°(H) 89°/89°(V)	89°/89°(H) 89°/89°(V)
Response Time	5ms (GTG)	5ms (GTG)
Sync	LVDS	LVDS
Power Consumption	160W	165W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	983.00 x 326.90 x 52.10	983.00 x 326.90 x 52.10
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL38S	JL38S
Weight	6,800 g	6,900 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

