

15" CCFL Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Low Power Consumption
- * Optional Touch Systems
- * CCFL 12 Lamps
- * VGA to XGA



JS150CPNN / JS150CKNN

Model	JS150CPNN	JS150CKNN
Display Type	LCD + Inverter	LCD + Inverter + AD/OSD Board
LCD Display	15" TFT LCD Module	15" TFT LCD Module
Base Panel Supplier	LG Display	LG Display
Base Panel Model	LM150X08	LM150X08
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	304.128 x 228.096 mm	304.128 x 228.096 mm
Brightness	2,000 cd/m ²	2,000 cd/m ²
Resolution	1024 x 768 (XGA)	1024 x 768 (XGA)
Contrast Ratio	800 : 1	800 : 1
Pixel Pitch (mm)	0.297 x 0.297	0.297 x 0.297
Viewing Angle	70°/70°(H) 75°/65°(V)	70°/70°(H) 75°/65°(V)
Response Time	8ms (Tr+Tf)	8ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	40W	45W
Temperature	Operation 0°C ~ +55°C Storage -20°C ~ +60°C	Operation 0°C ~ +55°C Storage -20°C ~ +60°C
Dimension(WxHxD)mm	326.50 x 253.50 x 11.20	326.50 x 253.50 x 11.20
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JC150	JC150
Weight	1,200 g	1,300 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)	JnM665	VGA + DVI + Audio(Optional)
	JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu

Sunlight Readable LCD Specialist !!!

