

15" LED Specifications

JNM DISPLAY Co., Ltd.

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch Systems
- * VGA to XGA



JS150LPNN / JS150LKNN

Model	JS150LPNN	JS150LKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	15" TFT LCD Module	15" TFT LCD Module
Base Panel Supplier	AUO	AUO
Base Panel Model	G150XG03 V2	G150XG03 V2
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	304.128 x 228.096 mm	304.128 x 228.096 mm
Brightness	1,500 cd/m ²	1,500 cd/m ²
Resolution	1024 x 768 (XGA)	1024 x 768 (XGA)
Contrast Ratio	700 : 1	700 : 1
Pixel Pitch (mm)	0.297 x 0.297	0.297 x 0.297
Viewing Angle	70°/70°(H) 65°/60°(V)	70°/70°(H) 65°/60°(V)
Response Time	8ms (Tr+Tf)	8ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	22W	27W
Temperature	Operation -30°C ~ +85°C Storage -40°C ~ +100°C	Operation -30°C ~ +85°C Storage -40°C ~ +100°C
Dimension(WxHxD)mm	326.50 x 253.50 x 12.00	326.50 x 253.50 x 12.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	JnM665 JnM665A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL150	JL150
Weight	1,100 g	1,200 g
Optional	Transflective tech.	Glass Bonding Touch

Specifications are subject to change without notice.

Control(AD) Board (Optional)

JnM665	VGA + DVI + Audio(Optional)
JnM665A	VGA + DVI + Composite + S-Video + Audio(Optional)

OSD Button

5 Key	Power Switch Select(+,-) Down Up Menu
-------	---------------------------------------

Sunlight Readable LCD Specialist !!!

